

# RELIABLE<sup>®</sup> STORAGE RACKS

*Rely On It!*

**... Positive Double Wedge Action**



**800-438-5629**

**visit our website for current pricing [www.huskyrack.com](http://www.huskyrack.com)**

Wireway Husky Corp. • 6146 Denver Industrial Park Circle • Denver, NC 28037  
Phone 704-483-1900 • Fax 704-483-1911 • [productinfo@wirewayhusky.com](mailto:productinfo@wirewayhusky.com)

© 2008, Wireway Husky Corp. All Rights Reserved.

# RELIABLE® STORAGE RACKS

## Featuring Positive Double Wedge Action

Reliable® storage racks are Wireway/Husky's answer to the popular Keystone punch style.

Reliable® features a single hole in the center of the upright face on a 3" centerline. Beams adjustable every 3". Beams from both sides share the same hole. Standard color is gray uprights with gray beams. Capacity based on 36" beam spacing.

## STANDARD UPRIGHT And BEAM SELECTION

Higher Uprights available up to 46 Ft.

### RELIABLE® UPRIGHT FRAME HEIGHTS

Dth	Cap. lbs.	6'	8'	10'	12'	13'	14'	15'	16'	18'	20'	22'	24'
36"	19,400	RU18-360-072	RU18-360-096	RU18-360-120	RU18-360-144	RU18-360-156	RU18-360-168	RU18-360-180	RU18-360-192	RU18-360-216	RU18-360-240	RU18-360-264	RU18-360-288
	25,000	RU24-360-072	RU24-360-096	RU24-360-120	RU24-360-144	RU24-360-156	RU24-360-168	RU24-360-180	RU24-360-192	RU24-360-216	RU24-360-240	RU24-360-264	RU24-360-288
42"	19,400	RU18-420-072	RU18-420-096	RU18-420-120	RU18-420-144	RU18-420-156	RU18-420-168	RU18-420-180	RU18-420-192	RU18-420-216	RU18-420-240	RU18-420-264	RU18-420-288
	25,000	RU24-420-072	RU24-420-096	RU24-420-120	RU24-420-144	RU24-420-156	RU24-420-168	RU24-420-180	RU24-420-192	RU24-420-216	RU24-420-240	RU24-420-264	RU24-420-288
48"	19,400	RU18-480-072	RU18-480-096	RU18-480-120	RU18-480-144	RU18-480-156	RU18-480-168	RU18-480-180	RU18-480-192	RU18-480-216	RU18-480-240	RU18-480-264	RU18-480-288
	25,000	RU24-480-072	RU24-480-096	RU24-480-120	RU24-480-144	RU24-480-156	RU24-480-168	RU24-480-180	RU24-480-192	RU24-480-216	RU24-480-240	RU24-480-264	RU24-480-288

### RELIABLE® BEAM LENGTH (CLEAR SPAN)

Beam size	48"	60"	72"	84"	92"	96"	108"	120"	144"
3.5" CAP.	RBX-35048 6,592#	RBX-35060 5,268#	RBX-35072 4,871#	RBX-35084 3,999#	RBX-35092 3,334#	RBX-35096 3,062#	RBX-35108 2,419#	RBX-35120 1,960#	RBX-35144 1,361#
3.9" CAP.	RBX-39048 7,849#	RBX-39060 6,273#	RBX-39072 5,801#	RBX-39084 4,965#	RBX-39092 4,408#	RBX-39096 4,048#	RBX-39108 3,198#	RBX-39120 2,590#	RBX-39144 1,799#
4.3" CAP.	RBX-43048 -	RBX-43060 7,244#	RBX-43072 6,700#	RBX-43084 5,735#	RBX-43092 5,232#	RBX-43096 5,010#	RBX-43108 4,026#	RBX-43120 3,261#	RBX-43144 2,265#
4.8" CAP.	RBX-48048 -	RBX-48060 -	RBX-48072 -	RBX-48084 6,929#	RBX-48092 6,322#	RBX-48096 6,054#	RBX-48108 5,373#	RBX-48120 4,412#	RBX-48144 3,064#

### RELIABLE® HEAVY DUTY BEAMS

5.5" CAP.	RBN-55048 -	RBN-55060 -	RBN-55072 -	RBN-55084 9,956#	RBN-55092 9,083#	RBN-55096 8,701#	RBN-55108 7,723#	RBN-55120 6,940#	RBN-55144 4,901#
6.0" CAP.	RBN-60048 -	RBN-60060 -	RBN-60072 -	RBN-60084 11,443#	RBN-60092 10,440#	RBN-60096 10,001#	RBN-60108 8,878#	RBN-60120 7,979#	RBN-60144 6,125#



Call 800-438-5629 or visit  
[www.wirewayhusky.com](http://www.wirewayhusky.com)

### UPRIGHTS AVAILABLE IN HEIGHTS UP TO 46 Ft.

- Notes:
- Standard depths are 36", 42", and 48". Other depths are available. Consult factory for pricing.
  - 1" x 1-1/2" horizontal bracing is placed approximately 8" from the floor to help resist impact damage and allow ease in lagging foot plate to floor.
  - Standard foot plates are punches with two 9/16" holes. The foot plate faces inward. Also available reversed.
  - Seismic and other options available.
  - Upright capacity based on 36" shelf spacing.